

# Category 6A Staggered Patch Panel, Unloaded - 1U



Staggered Patch Panel - C6A, 1U offers fast and reliable installation designed for 10G transmission requirement. The staggered design reduces Alien Crosstalk to support IEEE 802.3an and ANSI/TIA 568.2-D. Each port of the panel is numbered and having designated label area for clear port identification

#### **Features**

- Complies to ANSI/TIA-568.2-D, ISO/IEC 11801
- Staggered design reduces Alien Crosstalk
- 19" RJ-45 Patch Panel with 24 ports on 1U
- Strain relief and cable management
- Grounding bolt included
- Covered under 3C3<sup>®</sup> Performance Warranty

## **Mechanical Specifications**

Panel : Metal SPCC
Cabling Sequence : T568A & B
Testing Condition of Transmitting : 500MHz

Capability

Panel Thickness : Double layer - 2.5mm

Panel Color : Black
Each port Numbering : Yes
Grounding : Yes

### **Environmental Specifications**

Operating Temperature :  $-10^{\circ}\text{C to} + 60^{\circ}\text{C}$ Storage Temperature :  $-40^{\circ}\text{C to} + 70^{\circ}\text{C}$ Humidity :  $10^{\circ} - 90^{\circ}\text{RH}$ 

#### **Regulatory Compliances/Certifications**

- ETL Verified
- UL Listed
- RoHS Directive 2002/95/EC

#### **Ordering Information**

Product Code Description

11820 Copper Panel Staggered Shielded C6A, 24Port Unloaded 1U,

Wire manager included

Page 1 of 1

Kindly note that any specifications including design, measurements, size, dimension, weight and material specifications mentioned for different products across any technical or commercial document are subject to change by 3C3 India Pvt. Ltd., without any notice.

Document version: 11820/V1 Date of Revision: 04/2021 Log on to www.3c3.in for recent updates.

Phone: 080-48514828 / 23391755 | Email: sales@3c3.in | www.3c3.in